

2WAY Method Rim Lock
STANDARD OF RIM-LOCK

# MI-480S







\* The image is to aid in understanding and may differ from the actu



### REAL-TIME DOOR LOCK STATUS NOTIFICATION FUNCTION

#### **GUI THAT CAN BE UNDERSTOOD INTUITIVELY**

Usability UP for Comprehensive and Intuitive Icon Application!

It may be more convenient of use due to more comprehensible marks of Unlocked & Locked (Close) and Low Battery.



### NORMAL MODE & SAFETY MODE

#### SAFETY MODE WITH A PROTECTED MANAGER FUNCTION

Individual management for multiple cards in Safety mode

Normal Mode: Easy to use normal user.
 Safety Mode: High security mode with manager function added, provides individual register and delete function which is not provided in a normal mode.



## GUEST SECRET CODE (TEMPORARY USE)

#### TEMPORARY SECRET CODE FOR GUEST

#### A one-time usage password for guests

The Guest Secret Code is a one-time usage password that is automatically delete after it has been used, it can be set in 6 to 12 digits Safety Mode, and it can be utilized in situations that require special security functions such as when a guest makes a temporary visit.







MODEL NAME	MI-480S
POWER	DC 6 VOLT (AA.LR6 Alkaline Battery 8ea / Minimum 4ea)
PRODUCT SIZE (W x H x D)	Outer : 76 (W) x 163.6 (H) x 18.8 (D) mm   Inner : 154 (W) x 93 (H) x 37 (D) mm
PRODUCT MATERIAL	Aluminum Alloy Die-casting
EXTERNAL EMERGENCY POWER	When the Battery is Completely Discharged, Use 9v Battery to Open the Door.
PRODUCT COLOR	● Black